



Corner sofa (right side) with upholstered seat and back.

 0,53
  30,34
  1

	Back height	Seat height	Width	Depth
Measures mm.	725	430	800	800

Frame	Solid beech interior frame. 4-legged polypropylene base.
Seat	Solid beech structure with polypropylene elastic straps covered with flame retardant polyurethane flexible foam with a density between 25 kg/m ³ and 40 kg/m ³ .
Back	Beech plywood shell with flexible flame retardant foam with density between 25 kg/m ³ and 40 kg/m ³ .
Arms	Beech plywood covered with flexible flame retardant polyurethane foam with density between 25 kg/m ³ and 40 kg/m ³ .
Other materials	Zinc-nickel electrolyte screws. Galvanized staples. Polyvinyl acetate glue.

Leather	Leather
	L1 High grade cow leather
	L3 Polished full grain leather
	L6 Aniline leather batique-effect. Scandinavian cattle.

Fabrics

Fabrics / Telas

1 Jacquard One
Jacquard Three
Sand
Era
Gravity
Rivet
Urban

2 Jacquard Two

3 Jacquard Four
Medley
Revive 1
Maglia
Main Line Flax
Loom Two

4 Jacquard 4 Special
Hemp
Nexus
Oxygen
Floyd
Remix 2
Heritage
Savane
Loom Three
Loom Four

5 Silk
Synergy
Step
Step Melange
Messenger 5
Blazer
Melange Nap
Glow

6 Capture
Fiord
Tonus 4
Divina 3
Lopi

7 Canvas 2
Rime

8 Capture
Fiord
Tonus 4
Divina 3
Lopi

9 Divina MD
Divina Melange 3
Hallingdal 65
Steelcut Trio 3

Faux Leather / Ecopiel

1 Valencia
2 Silvertex
4 Dolce
6 Ledger

Resistance and Quality

Indoor Air Quality-Advantage Gold

ISO 9001

UNE-EN 16139

Fireproof

BS 5852 Part 2 Crib 5

Sustainability

FSC

ISO 14001

ISO 14001

level® 1 certified to ANSI/BIFMA e3 Standard



Corner sofa (right side) with upholstered seat and back.

 0,63
  32
  1

	Back height	Seat height	Width	Depth
Measures mm.	725	430	965	800

Frame	Solid beech interior frame. 4-legged polypropylene base.
Seat	Solid beech structure with polypropylene elastic straps covered with flame retardant polyurethane flexible foam with a density between 25 kg/m ³ and 40 kg/m ³ .
Back	Beech plywood shell with flexible flame retardant foam with density between 25 kg/m ³ and 40 kg/m ³ .
Arms	Beech plywood covered with flexible flame retardant polyurethane foam with density between 25 kg/m ³ and 40 kg/m ³ .
Other materials	Zinc-nickel electrolyte screws. Galvanized staples. Polyvinyl acetate glue.
Leather	<p>Leather</p> <p>L1 High grade cow leather</p> <p>L3 Polished full grain leather</p>

Fabrics

Fabrics / Telas

1 Jacquard One
Jacquard Three
Sand
Era
Gravity
Rivet
Urban

2 Jacquard Two

3 Jacquard Four
Medley
Revive 1
Maglia
Main Line Flax
Loom Two

4 Jacquard 4 Special
Hemp
Nexus
Oxygen
Floyd
Remix 2
Heritage
Savane
Loom Three
Loom Four

5 Silk
Synergy
Step
Step Melange
Messenger 5
Blazer
Melange Nap
Glow

6 Capture
Fiord
Tonus 4
Divina 3
Lopi

7 Canvas 2
Rime

8 Capture
Fiord
Tonus 4
Divina 3
Lopi

9 Divina MD
Divina Melange 3
Hallingdal 65
Steelcut Trio 3

Faux Leather / Ecopiel

1 Valencia
2 Silvertex
4 Dolce
6 Ledger

Resistance and Quality

Indoor Air Quality-Advantage Gold

ISO 9001

UNE-EN 16139

Fireproof

BS 5852 Part 2 Crib 5

Sustainability

FSC

ISO 14001

ISO 14001

level® 1 certified to ANSI/BIFMA e3 Standard



Corner sofa (left side) with upholstered seat and back.

 0,53
  30,34
  1

	Back height	Seat height	Width	Depth
Measures mm.	725	430	800	800

Frame	Solid beech interior frame. 4-legged polypropylene base.
Seat	Solid beech structure with polypropylene elastic straps covered with flame retardant polyurethane flexible foam with a density between 25 kg/m ³ and 40 kg/m ³ .
Back	Beech plywood shell with flexible flame retardant foam with density between 25 kg/m ³ and 40 kg/m ³ .
Arms	Beech plywood covered with flexible flame retardant polyurethane foam with density between 25 kg/m ³ and 40 kg/m ³ .
Other materials	Zinc-nickel electrolyte screws. Galvanized staples. Polyvinyl acetate glue.

Leather	Leather
	L1 High grade cow leather
	L3 Polished full grain leather
	L6 Aniline leather batique-effect. Scandinavian cattle.

Fabrics

Fabrics / Telas

1 Jacquard One
Jacquard Three
Sand
Era
Gravity
Rivet
Urban

2 Jacquard Two

3 Jacquard Four
Medley
Revive 1
Maglia
Main Line Flax
Loom Two

4 Jacquard 4 Special
Hemp
Nexus
Oxygen
Floyd
Remix 2
Heritage
Savane
Loom Three
Loom Four

5 Silk
Synergy
Step
Step Melange
Messenger 5
Blazer
Melange Nap
Glow

6 Capture
Fiord
Tonus 4
Divina 3
Lopi

7 Canvas 2
Rime

8 Capture
Fiord
Tonus 4
Divina 3
Lopi

9 Divina MD
Divina Melange 3
Hallingdal 65
Steelcut Trio 3

Faux Leather / Ecopiel

1 Valencia
2 Silvertex
4 Dolce
6 Ledger

Resistance and Quality

Indoor Air Quality-Advantage Gold

ISO 9001

UNE-EN 16139

Fireproof

BS 5852 Part 2 Crib 5

Sustainability

FSC

ISO 14001

ISO 14001

level® 1 certified to ANSI/BIFMA e3 Standard



Corner sofa (left side) with upholstered seat and back.

 0,63
  32,44
  1

	Back height	Seat height	Width	Depth
Measures mm.	725	430	965	800

Frame	Solid beech interior frame. 4-legged polypropylene base.
Seat	Solid beech structure with polypropylene elastic straps covered with flame retardant polyurethane flexible foam with a density between 25 kg/m ³ and 40 kg/m ³ .
Back	Beech plywood shell with flexible flame retardant foam with density between 25 kg/m ³ and 40 kg/m ³ .
Arms	Beech plywood covered with flexible flame retardant polyurethane foam with density between 25 kg/m ³ and 40 kg/m ³ .
Other materials	Zinc-nickel electrolyte screws. Galvanized staples. Polyvinyl acetate glue.

Leather	Leather
	L1 High grade cow leather
	L3 Polished full grain leather
	L6 Aniline leather batique-effect. Scandinavian cattle.

Fabrics

Fabrics / Telas

1 Jacquard One
Jacquard Three
Sand
Era
Gravity
Rivet
Urban

2 Jacquard Two

3 Jacquard Four
Medley
Revive 1
Maglia
Main Line Flax
Loom Two

4 Jacquard 4 Special
Hemp
Nexus
Oxygen
Floyd
Remix 2
Heritage
Savane
Loom Three
Loom Four

5 Silk
Synergy
Step
Step Melange
Messenger 5
Blazer
Melange Nap
Glow

6 Capture
Fiord
Tonus 4
Divina 3
Lopi

7 Canvas 2
Rime

8 Capture
Fiord
Tonus 4
Divina 3
Lopi

9 Divina MD
Divina Melange 3
Hallingdal 65
Steelcut Trio 3

Faux Leather / Ecopiel

1 Valencia
2 Silvertex
4 Dolce
6 Ledger

Resistance and Quality

Indoor Air Quality-Advantage Gold

ISO 9001

UNE-EN 16139

Fireproof

BS 5852 Part 2 Crib 5

Sustainability

FSC

ISO 14001

ISO 14001

level® 1 certified to ANSI/BIFMA e3 Standard