



Stackable chair with oak board seat and backrest and solid beech wood. Option of fully upholstered shell or upholstered shell pad.

0.304 m³ 8.5 kg
 10.74 Ft 18.74 Lbs

	Backrest height	Seat height	Width	Depth
Measures (mm)	790	455	500	500

- Frame** Solid ash legs and frame.
- Seat** Oak board. Option of fully upholstered seat and back or upholstered shell pad covered with flexible flame retardant polyurethane foam with density between 25 kg/m³ and 40 kg/m³.
- Accessories** Polypropylene, felt or steel glides.
- Other materials** Zinc-nickel electrolyte screws. Galvanized screws. Polyvinyl acetate glue.

Fabrics / Telas

- 1** Soft-fiber
 Jacquard One
 Jacquard Three
 Citadel
 Sand
 Era
 Gravity
 Rivet
 Urban
- 2** Jacquard Two
 Solid & Stripes
 Loom One
 Circular One Pure Eco
- 3** Jacquard Four
 Medley
 Revive 1
 Natte
 Main Line Flax
 Loom Two
 Mezzo

- 4** Jacquard 4 Special
 Nexus
 Field 2
 Floyd
 Remix 3
 Heritage
 Savane
 Loom Three
 Loom Four
 Cura
 Oceanic
- 5** Silk
 Synergy
 Step
 Step Melange
 Blazer
 Melange Nap
 Glow
 Chili
 Noma
 Re-wool

- 6** Go check
 Swing
 Chartres
 Loom Five
 Zori
 Patio
- 7** Canvas 2
 Rime
 Select
 Clara 2
- 8** Capture
 Fiord 2
 Tonus 4
 Divina 3
 Lopi
 Domino
- 9** Divina MD
 Divina Melange 3
 Hallingdal 65
 Steelcut Trio 3

Faux Leather / Ecopiel

- 1** Valencia
2 Silvertex
3 Maglia
4 Dolce
8 Ultraleather Original
 Ultraleather Linen
 Ultraleather Pearlized
9 Brisa Original
 Brisa Distressed
 Brisa Fresco
 Brisa Mokume
 Ultraleather Cora Outdoor
 Ultraleather Pony
 Ultraleather Pro
 Ultraleather Promessa
 Ultraleather Promessa Outdoor
 Ultraleather Dwell
 Ultratech EcoTech
10 Brisa Distressed Outdoor
 Ultraleather Distressed Outdoor
 Ultratech Helix
 Ultratech Wired

- 11** Ultraleather Reef Pro
 Ultraleather Volar Bio
 Ultratech Cove

Upholstery

Leather / Piel

- L1** High grade cow leather
Piel de vaca de 1ª categoría
- L3** Polished full grain leather
Plena flor pulida
- L6** Aniline leather batique-effect.
Scandinavian cattle.
Piel anilina efecto batique.
Ganado escandinavo.

Leather

RESISTANCE AND QUALITY

UNE-EN 16139:2013
ISO 9001

FIREPROOF

UNE-EN 1021-1:2006
B.S. 5852 Part 2 Crib V
UNI 9175 M-1
California Tech.Bulletin 117

SUSTAINABILITY

FSC
ISO 14001
level® 2 certified to ANSI/BIFMA e3 Standard