

Stackable armchair with oak board seat and backrest and solid beech wood. Wide version. Option of fully upholstered shell or upholstered shell pad.



10.5 kg 23.15 Lbs

Measures	
(mm)	

Backrest height	Seat height	Arm height	Width	Depth
790	455	650	640	570

Solid ash legs and frame.

Seat

Frame

Oak board. Option of fully upholstered seat and back or upholstered shell pad covered with flexible flame retardant polyurethane foam with density between 25 kg/m3 and 40 kg/m3.

Accesories

Polypropylene, felt or steel glides.

Other materials

Zinc-nickel electrolyte screws. Galvanized screws. Polyvinyl acetate glue.

Upholstery

Fabrics / Telas

Jacquard One

Jacquard Three

1 Soft-fiber

Citadel

Sand

Gravity

Rivet

Era

- 4 Jacquard 4 Special Nexus Field 2 Floyd Remix 3 Heritage Savane Loom Three Loom Four Cura Oceanic
- 5 Silk Synergy Step Step Melange Blazer Melange Nap Glow Chili Noma

Re-wool

- 6 Go check Swing Chartres Loom Five 7ori Patio 7 Canvas 2
- Rime Select Clara 2 8 Capture Fiord 2 Tonus 4

Divina 3

Lopi

Domino 9 Divina MD Divina Melange 3 Hallingdal 65 Steelcut Trio 3

Faux Leather / Ecopiel

- 1 Valencia
- Silvertex
- 3 Maglia 4 Dolce
- 8 Ultraleather Original Ultraleather Linen Ultraleather Pearlized
- 9 Brisa Original Brisa Distressed Brisa Fresco Brisa Mokume Ultraleather Cora Outdoor Ultraleather Pony Ultraleather Pro Ultraleather Promessa Ultraleather Promessa Outdoor Ultraleather Dwell
- Ultratech EcoTech 10 Brisa Distressed Outdoor Ultraleather Distressed Oudoor Ultratech Helix Ultratech Wired

11 Ultraleather Reef Pro Ultraleather Volar Bio Ultratech Cove

Andreu World

SO3023 Solo Chair Philippe Starck

Leather / Piel

- **L1** High grade cow leather Piel de vaca de 1ª categoría
- L3 Polished full grain leather Plena flor pulida

L6 Aniline leather batique-effect. Scandinavian cattle. Piel anilina efecto batique. Ganado escandinavo.

Leather

RESISTANCE AND

QUALITY

ISO 9001

FIREPROOF

UNE-EN 1021-1:2006

UNE-EN 16139:2013

B.S. 5852 Part 2 Crib V

UNI 9175 M-1

California Tech.Bulletin 117

SUSTAINABILITY

FSC

ISO 14001

level® 2 certified to ANSI/BIFMA e3 Standard